



Eyers Grove Management Group, Inc.
 18 Eyersgrove Road Millville, PA 17846
 Ph: 570-458-7039 Fax: 570-458-7039
 Email: sales@eyersgrove.net

CT Modular Wiring Head Request Specifications

Ordering Information

MODULAR WIRING HEADS FOR RTD'S AND TRANSMITTERS

PRODUCT CODE		CONNECTION / CABLE (Includes water tight cord grip)
STYLE		00 No cable (Std.)
1 Standard		05 25ft
2 Standard (with health authority seal provision)		10 50ft
3 Mini (for RTD and analog transmitter)		15 75ft
4 Mini (with health authority seal provision)		20 100ft
7 Standard, Dual Output		
8 Standard, Dual Output (with health authority seal provision)		
		(Quick Disconnect Options) ^{***†}
MODULE*		A0 QDR only
Single Output Options		A1 QDR & Field Wireable Connector (FWC)
0 No Module		A2 QDR / FWC w/ 25ft
1 Single RTD		A3 QDR / FWC w/ 50ft
2 Dual RTD		A4 QDR / FWC w/ 75 ft
3 4-20mA Analog transmitter (head style 1 or 2 only)		A5 QDR / FWC w/ 100ft
4 "SMART" Module with 4-20 mA and HART (head style 1 or 2 only)		1 FIXED CHARACTER
5 4-20mA Mini transmitter (head style 3 or 4 only)		PRE-WIRED ELEMENT (refer to picture below for orientation)
6 4-20mA Mini transmitter (head style 3 or 4 only) (for use with probe lengths of 1.25" or less)		0 None
		1 Vertical Orientation (option "A")
Dual Output Options		2 Horizontal Orientation (option "B")
A Dual 4-20mA Temperature Transmitter		
B Dual Smart with 4-20mA with "HART"		
C 4-20mA Temperature Transmitter & RTD		
D Smart 4-20mA with "HART" & RTD		
E 4-20mA Temp. Transmitter & Smart 4-20mA with "HART" Transmitter		
		* To order only the output module, consult our Customer Service Department.
OUTPUT RANGE		"SMART" Module Part Number: 5610100003
000 None (RTD only)		** This range available with display options 00, 01, 02 only.
069 0-60 (C only)		*** Not available with output range 000.
071 0-100 (F or C)		† Not available with Dual Output
073 0-150 (F or C)		
075 0-200 (F only)		
076 0-250 (F only)		
077 0-300 (F only)		
119 30-230 (F only)**		
132 50-250 (F only)**		
160 100-300 (F only)		
255 0-180 (C only)		
999 Programmable (Module Style 4, B, and D only)		

Other Notes:
